

<u>Miramar</u> _TM

4802X

WIDESPREAD LAVATORY FAUCET

Features Available in 28 finishes including 13 PVD finishes All brass construction 6" spout center to center 1/4 turn ceramic disc cartridge(s) Flexible braided hoses for ease of installation ϕ 1-1/4" all brass touch style pop up drain assembly 1.2 gpm (4.5 L/min) max flow rate aterSe **Codes/Standards** Product meets or exceeds the following: ASME A112.18.1/CSA B125.1 NSF/ANSI 61 & NSF/ANSI 372 CEC / DOE EPA WaterSense High Efficiency Lavatory Commonwealth of MA 8" MINIMUM [203] $10\frac{1}{8}$ 6" [152] [257] $1\frac{1}{2}$ " [38] $5\frac{5}{16}$ [135] 3 16 2-5 16" MIN STEM HEIGHT [78] $3X \phi 2 \frac{5}{16}$ " [59] [59] 1<u>9</u> MAX [40] 2<u>15</u>" MAX [74] $\phi 2\frac{3}{16}$ 0 [56] 1/2" NPSM 3 $2\frac{1}{8}$ " MAX [76] [54] 3/8" COMPRESSION FITTING $6\frac{5}{16}$ THROUGH-HOLE SPECIFICATIONS [160] $\frac{5}{8}$ MIN RECOMENDED MAX $\phi^2 \frac{5}{16}$ $0^{1\frac{1}{4}}$ [15] SPOUT: Ø11/16" [17] VALVE: Ø1" [25] Ø 1-3/8" [35] Ø 1-3/8" [35] Ø 1-1/2" [38] Ø 1-1/2" [38] [59] [32] TOP OF HANDLE DIMENSIONS SHOWN TO NEAREST 1/16" SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE [DIMENSIONS SHOWN TO NEAREST 1mm]

4802X sp 200827