# 388-386RH SUMMIT®

# 

Round Front, SmartHeight™, Vitreous China, Two-Piece Toilet

### FEATURES

- High performance MagnaFlush<sup>™</sup> flushing technology
- 1.6 gpf / 6.0 lpf low water consumption
- Round front, SmartHeight<sup>™</sup> bowl
- SmartFasten<sup>™</sup> 3-bolt tank-to-bowl connection
- PuraClean<sup>®</sup> easy-to-clean glaze
- 3' Rigid Flapper flush valve requires less force to flush, is more consistent and uses a simple universal repair part/seal
- Fluidmaster<sup>®</sup> pilot operated anti-siphon fill valve
- 12' rough-in
- Model 57RH chrome-plated, metal trip lever
- · 2' glazed trapway
- The Mansfield® limited lifetime warranty on china; Five-year limited warranty on tank trim
- · Available in White

# MDDEL 388-386RH Toilet seat not included

### COMPONENTS

MODEL #	DESCRIPTION	CODES/STANDARDS	
388-386RH	Round front, SmartHeight™, two-piece toilet. Less toilet seat and supply.		
388	Round front, SmartHeight <sup>™</sup> toilet bowl only. Less supply. Specify color. Tank and cover only with right hand, chrome-plated, metal trip lever. Less supply.		
386RH			
TANK TRIM & R	EPLACEMENT PARTS		
57RH	Trip lever - chrome-plated, metal trip lever, right hand		
2037-1212	Summit® 1.6 rigid flapper flush valve		
400A	Fluidmaster® anti-siphon pilot fill valve		
2206	Anti-siphon pilot fill valve (compatible replacement)		
630-0030	Replacement flush valve seal		
386-LID	Tank lid		

When properly installed, this product meets the requirements for the Americans with Disabilities Act of 1990 (ADA). Refer to local plumbing codes, as they may vary by location and application.



# 388-386RH **SUMMIT**®

Round Front, SmartHeight™, Vitreous China, Two-Piece Toilet

### **SPECIFICATIONS**

TANK OPTIONS

MODEL #	DESCRIPTION	CODES/STANDARDS
388-386RH	Round front, SmartHeight™ (1.6 gpf/6.0 lpf) two-piece toilet	

MATERIAL	Vitreous China
WATER PRESSURE RANGE	20 to 80 PSI
FLUSH SYSTEM	MagnaFlush™ flushing technology
WATER USAGE	1.6 gpf / 6.0 lpf
WATER SURFACE AREA	8'X9'
ROUGH-IN	12'
MAP RATING	1,000 grams

TRAP DIAMETER	2'
TRAP SEAL	2-1/4'
SHIPPING WEIGHT	Model 388 - 52 lbs. (23.5 kg) Model 386RH - 36 lbs. (16.3 kg)
WARRANTY	Vitreous China - Limited Lifetime Tank Trim - Limited Five Year

### **TECHNICAL INFORMATION** Note: these dimensions are nominal and subject to change without notice.

386	Variation of model 386RH, with right hand trip lever.	FINISHED WALL
386LT	Variation of model 386, with tank liner.	12-3/4" 3/4" (19 MM) 27-3/8" (19 MM) (19 MM) (19 MM) (19 MM) (19 MM) (10 MM
		(695 MM) 8-1/4" (210 MM) 5-13/16" (148 MM) (148 MM) (148 MM) (148 MM) (148 MM) (148 MM) (148 MM) (148 MM) (10 MM) (148 MM) (10 MM) (10 MM) (10 MM) (10 MM) (10 MM) (10 MM) (11 MM) (11 MM) (11 MM) (12" (10 MM) (12" (130 MM) TYP.

TYP.

Fixture performance and specifications meet or exceed ASME A112.19.2/CSA B45.1 standards, and other state and local codes.